

Congratulations on the purchase of your new **RANGEVIEW™ ED** Spotting Scope!

There are a few simple steps to fully assemble your new spotting scope. Follow the below instructions before use.

Attaching the Eyepiece:

1. Remove the eyepiece and spotting scope from the packaging foam.
2. Take the rubber cover off the eyepiece bottom & top of the spotting scope. Keep these covers for future use.
3. Thread the eyepiece into the spotting scope body using the knurled locking ring on the eyepiece. When fully seated, tighten the knurled locking ring by hand until firm.

Note: If the eyepiece is not tightly seated, the zoom indicator line will not stay stationary and will rotate with the eyepiece body. Tighten the eyepiece locking ring until firmly seated and zoom indicator does not move when adjusting the zoom.



Installing the Carry Bag:

1. Open the top flap of the bag that is secured with Velcro.
2. Unzip the long zipper on the left side so it is open fully.
3. Place the spotting scope into the bag objective lens first, making sure the mounting platform and focus knobs are accessible through their corresponding access holes.
4. Zip up the bag and re-close the top Velcro flap when not in use.

Using the **RANGEVIEW™ ED** Spotting Scope:

1. Follow the included Users Guide on page 2 that describes attaching the scope to a tripod.
2. Next, unzip the side zipper half way and secure the bag flaps using the metal snaps on each side of the bag as shown.
3. Unzip the front lens bag zipper near the front lens and push the bag flap out of the way.
4. Open the top Velcro flap to access the focus knobs.
5. Remove the lens covers on the objective lens and eyepiece.

Note: In this configuration, the spotting scope zoom and orientation can be adjusted while in the bag. To reorient the eyepiece into a new position, loosen the optical tube lock knob located on the right side and rotate to the desired position. Tighten the lock knob when done.

